

LVM 8 · LOW VOLTAGE MODULE · PRELIMINARY

# LVM 8

Modular LFP Battery Storage · 16 – 480 kWh scalable

A modular low-voltage battery system built for safety, longevity and simple installation. Compatible with leading hybrid inverters and scalable from a single 16 kWh tower to 480 kWh in parallel.

## Product Highlights

- Scalable from 16 kWh to 480 kWh
- Compatible with Victron, Solis, Deye and Hoymiles inverters
- LFP battery chemistry — maximum safety and long life (8000 cycles @ 25 °C)
- Modular design simplifies transport and installation
- Steel housing, no additional wiring required

## Configurations

Modules are installed in pairs. Up to 6 modules stack on top of each other to form a tower, and up to 10 towers can be connected in parallel for a maximum system size of 480 kWh.

	16 kWh	32 kWh	48 kWh
<b>Number of Modules</b>	2	4	6
<b>Usable Energy</b>	16 kWh	32 kWh	48 kWh
<b>Max Cont. Current *</b>	80 A	160 A	180 A
<b>Dimensions H × W × D</b>	608 × 800 × 260 mm	1108 × 800 × 260 mm	1608 × 800 × 260 mm
<b>Weight</b>	124.8 kg	239.6 kg	364.4 kg

Tower 2x — 16 kWh · Tower 4x — 32 kWh · Tower 6x — 48 kWh

*\*Maximum current may be thermally throttled to protect cell life. Under heavy or continuous use, power output may be temporarily reduced.*



Figure 1: LVM 8 MODULE – 8 kWh



Figure 2: 6 × LVM 8 MODULE – 48 kWh

## Technical Parameters

All values are valid for all tower configurations unless stated otherwise.

<b>Battery Module</b>	LVM 8 (8 kWh, 51.2 V, 58.4 kg)
<b>Battery Cell Technology</b>	LiFePO4
<b>Nominal Voltage</b>	51.2 V
<b>Operating Voltage</b>	44 – 57.6 V
<b>Operating Temperature</b>	-10 °C to +40 °C
<b>Round-Trip Efficiency</b>	≥ 95 %
<b>Life Cycles</b>	8000 cycles @ 25 °C
<b>Inverter Communication</b>	CAN
<b>Parallel Communication</b>	RS485
<b>Smart Home Integration</b>	Ethernet
<b>Enclosure Protection</b>	IP 20
<b>Certification</b>	VDE2510-50 / CE / UN38.3
<b>Warranty</b>	8 Years
<b>Compatible Inverters</b>	Solis Hybrid, Deye Hybrid, Victron, Hoymiles

### SAFETY & SIMPLICITY

**LFP chemistry, steel enclosure, easy setup with no additional wiring — the LVM 8 is designed for maximum safety, long service life and a clean installation.**

*All specifications are preliminary and subject to change without notice. © MEDA GmbH — li.energy*